

Heat Detector

Rapid Detection Where it Matters



Headache Free

Thermistor-based sensing technology ideal for garage and kitchen installations



Easy Maintenance

Easily open device to assist in your regular deep cleaning process



Smart Detection

Fixed temperature and rate of rise detection



Early Awareness Early low battery notification



Chirp Control

Silence fault chirps for up to 12 hours, and nuisance alarms for up to 10 minutes



Long Battery Life Up to 6 year battery life with normal usage











SPECIFICATIONS	
Sensor Types	Thermistor: High temperature range $135^{\circ}F \pm 4^{\circ}F$ or $58^{\circ}C \pm 4^{\circ}C$ ROR: $15^{\circ}F$ / min when > $104^{\circ}F$ or $8.3^{\circ}C$ / min when > $40^{\circ}C$ Photoelectric (Optical)
Integrated Head Removal Tamper Switch	When head is removed a signal can be sent to the panel/hub via the RF module
Sound Level	Minimum output 85dBA at 3m. The sounder contacts are soldered directly to the piezo disc for additional security
Button Test	Checks the sensors, electronics, battery and horn
Silence Function	Silences nuisance alarm (automatically resets after approximately 10 minutes)
Power Source	2 x CR123A battery
LED Indicators	RED - Power up, button test, in alarm, in hush, memory YELLOW - Power up, low battery, sensor fault, end of life
Operating Temperature	PGP9979 (UL): 4.4°C to 48.8°C (40°F - 120°F¹)
	PGP8979 (CE) Normal: -10°C to 40°C (14°F - 104°F¹)
Humidity Range	15% - 95% Relative Humidity (non-condensing)
Product Dimensions	120mm (4.7") x 46mm (1.8")
Weight	7.05 ounces or 200g (including packaging)

¹Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as requird by the specific Product Standards. However, extended exposure to conditions outside these ranges may affect product life. For advice on prolonged operation outside these ranges consult the manufacturer.

MODEL VARIATIONS	
SMD-979 ME PGP (868-0:025)	SMD-979 ME PGP Wireless Heat Detector 868 MHz
SMD-979 PGP (868-0:025)	SMD-979 PGP Wireless Heat Detector 868 MHz
PGP9979	PGP9979 PGP Wireless Heat Detector 915 MHz
PGP8979	PGP8979 PGP Wireless Heat Detector 868 MHz

COMPATABILITY	
Panel	IQ Panel 4, IQ4 Hub, IQ4 NS, PowerSeries Neo, PowerSeries Pro, IQ Pro, PM v20







